

DOCUMENT NO.

10041118

04/30/1998

JAPANESE PATENT ABSTRACT JP10041118 A 19980213

REFERENCE AN

Best Available Copy

© PAJ / JPO

PN -JP10041118 A 19980213

-MAGNETIC POWDER FOR MAGNETIC RECORDING MEDIUM,
MAGNETIC CARD USING MAGNETIC POWDER, AND
MANUFACTURE OF MAGNETIC CARD

AB -PROBLEM TO BE SOLVED: To increase a coercive force and obtain excellent dispersion in magnetic coating by hydrogenating magnetic powder comprising rare earth elements, including Y which is expressed by a specific expression and includes Sm as its essential component, and a transition metal including the main component of Co, within a specific temperature range, before the coating is formed by using the magnetic powder.

- -SOLUTION: The magnetic powder is expressed by Rx T100-x-y My (R designates at least one element selected from rare earth elements including Y which includes Sm as its essential component, T designates at least one element selected from a transition metals Fe, Co, Ni including Co as its main component, and M designates at least one of Si, Ti, Al, Ga, V, Cr, Mn, Cu, Zr, Nb, Mo, Pd, Hf, Ta, W, Pt and Au. The composition value x of R is 16.0-22.0(at%), the composition value y of M is 0<=y<30.0 (at%)). Before the coating is formed by using the magnetic powder, the msqnetic powder is hydrogenated within a temperature range from the liquid nitrogen temperature to 200 deg.C.
- -H01F1/20 ;B22F1/00 ;C08J7/04 ;C22F1/10 ;G11B5/842

PA - TOKIN CORP

IN - ANPO TAMIKO; HASEBE AKIO

ABD -19980430

ABV -199806

AP -JP19960209241 19960718

none

попе

none